AT54 SERIES

54522FLS

WHEAT ELASTIC SIDED BOA BOOT



STYLE SPECIFICATIONS

DESCRIPTION:
All terrain water resistant nubuck leather composite toe cap safety boot.

COLOUR:
Wheat

SIZES (UK/AU):
3 – 15, 6 ½ - 12 ½

STANDARDS:
AS 2210.3:2019
EN ISO 20345:2022
AMD 1:2024

APPLICATON:

- Agriculture
- Building & Construction
- Manufacturing
- Transport & Logistics
- Warehousing
- Metals Industry
- Mining & Quarrying

FEATURES

- Water resistant nubuck leather.
- **BOA®** Fit System delivers micro-adjustable, precision fit, engineered and guaranteed to perform in the toughest conditions.
- **TEC*tuff*®** toe bumper to protect against scuffing.
- **COOL*step*®** lining to absorb moisture and odour for optimum freshness and hygiene.
- **HEEL*guard*®** for added stability and increased durability.
- Heavy duty **Kevlar®** stitching across critical wear seams for maximum abrasion and chemical resistance.
- **COMFORT*cushion*®** Impact Absorption System Insole with **PORON®** protects the heel and ball of the foot.
- **NATURE*form*®** composite toe cap with a wide profile for greater comfort.
- **NANO*lite*®** footbed with memory foam to help reduce fatigue.
- Oliver **SOFT*stride*®** open cell low density urethane foam built into the insole for ultimate comfort and contour support.
- Driver-centric stabiliser ensures optimised foot positioning for comfort and control while driving.
- Certified ladder grip zones offer secure, slip-resistant footing on ladders for improved safety.
- Enhanced lateral grip ensures stable footing and confidence during side to-side movements.
- Programmed deformation zones in the sole provide advanced cushioning and rebound, delivering extra shock absorption for all-day comfort.
- Stop & hold technology delivers reliable steadiness on uneven or inclined surfaces, helping prevent slips and falls.
- Excellent slip resistant sole; SRC slip resistant classification. Anti-static.
- AT's dual density PU/Rubber sole with lightweight shock absorbing PU midsole & hardwearing rubber **BOA®** Fit System outsole for superior durability. Resistant to 300˚C surface contact.
- Deep tread profile, with a self-cleaning design delivers superior traction in the roughest of terrain.
- Sole resistant to mineral and organic oils & acids. Cut, split and crack resistant.

COMFORT TECHNOLOGY

- COMFORT*cushion* Impact Absorption
- NATURE*form* wide profile Type 1 safety toe cap
- Water Resistant leather
- Non-Metallic Composite Toecap
- NANO*lite* footbed
- SOFT*stride* Contour Comfort Support
- Antimicrobial Technology
- HEEL*guard*
- BOA® Fit System
- Toe Bumper

SOLING TECHNOLOGY

- 300°C Heat Resistant sole (572°F)
- Abrasion Resistant sole
- Cut Resistant sole
- Slip Resistant sole
- Sole resistant to mineral oils and acids
- Sole resistant to organic oils and fats
- Antistatic discharges static build-up

PIP GLOBAL SAFETY
Oliver Footwear. Level 5 163-175 O'Riordan Street Mascot NSW 2020
Tel: 1300 747 269 (1300 PIP ANZ)
Email: cs@pipanz.com
www.oliver.com.au
oliversafetyfootwear
@oliver.boots